

2009

HOT FARM 466 9500# & 10,000# TRACTOR – 2 hooks only

1. Motor and Turbo Charger Limitations:
 - a. **600** cubic inches-Maximum for 2007 members, weight 9500# & 10,000#
 - b. Fuel pump-P –Pump
 - c. One turbo charger per tractor-specifications: 3” inlet and 3” outlet
MAXIMUM; No sleeves, no slots. Maximums will be measured at the wheel face. (Inlet and Outlet)-air wheels must protrude into the inlet and outlet openings. Small base. No NTPA exceptions.
 - d. Diesel Fuel ONLY
 - e. Air has to take shortest route from Turbo to intake.
2. OME Stock INTAKE and Stock EXHAUST Manifolds ONLY.
3. Water:
 - a. Water Injection ONLY
 - b. NO ALCOHOL (i.e., Methanol, Ethanol and etc.) Water injection PUMP lubrication oil is ACCEPTABLE
4. Motor Appearance:
 - a. Stock engine Block, No Deck Plate(s), Stock Heads –No steel Billet or Aluminum heads.
 - b. No inner coolers allowed.
5. Transmission:
 - a. Factory transmission. No bolt-in transmissions, Gear changes inside Transmission are acceptable.
6. Tire size:
 - a. 20.8 x 38 maximum, **double cut tires allowed, radial or bias ply.**
7. Roll cages are required for 2009.
8. Evaluate weights after 3 pulls.
9. Wheelie bars, frame tie bars, side shields, 3/8 inch bolt cross in exhaust pipe, seat belts, dead man’s throttle.
10. **2007 members have until end of 2009 to become 466 cubic inch. All Hot Farm Tractors must be 466 for 2010 pulling season. New pullers in Hot Farm 2008 or 2009 must be 466 cu inch. This rule is non-amendable.**
11. **General rules also apply**