

2010

MODIFIED V-8 6000 & 6200 SINGLE CARB TRACTORS 2 HOOKS ONLY

1. One automotive block not to exceed 485 C.I.D.
2. One stock 850 CFM carburetor choke horn intact, no thin throttle shafts, no thinned butterflies, stock base plates—carbs will be removed after pull and inspected by Steve Call.
3. Gasoline fuel only
4. Wide front needed
5. 24.5 tire size
6. Tri-State rules apply (shielding and lead blankets) Roller Cams Allowed
7. One stock type intake not to exceed 5" from top of head to bottom of carburetor
8. No aluminum or Hemi heads allowed
9. Engine protest will cost \$100.00. If illegal money goes to protestor. If legal money goes to owner of protested vehicle.
10. Reverse lockout on automatic transmission are required.
11. Neutral start switches are required
12. All tractors must have fenders of a shield between the driver and tires to consist of a solid barrier between driver and any part of rear tires sufficient to support weight of driver. Must be a minimum of 36" long at top and must curl a minimum out over tire.
13. Planetary rear ends are allowed
14. No radial tires or double cut tires
15. Electric fuel pump(s) must have shut off with kill switch and shut off from the driver's seat.
16. Roll cage required.
17. If protested all V-8's must have 2 oil pan bolts and 2 intake bolts drilled so the engine can be sealed.
18. If protested vehicle must go to neutral location and held until tore down, or tore down at time of event.
19. All tractors must have a full roll cage of **.120** thickness tubing.
20. If moving over 200# from one location to another on a vehicle you must rescale.
21. Any vehicle can have his engine cubed before the season starts and have his engine sealed, if desired.
22. No portion of tractor may exceed 14 feet forward of the center of the rear wheel.
23. General Rules also apply.